



TECHNICAL DATA

Veedol Syntron TGI 5W-30

1 Litre

PRODUCT DESCRIPTION

SYNTRON TGI 5W-30 is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbo-charged engines. SYNTRON TGI 5W-30 is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ILSAC: GF-5

GM: dexos 1™ Gen 2

API: SN-RC, SN, SN Plus, SM/SL

SIZE	PART NO	BARCODE
1 Litre	5630	5020618056300

PRODUCT BENEFITS

- * Helps resolve LSPI issues
- * Fuel Efficient
- * Fully Synthetic

DIRECTIONS FOR USE

Use as per manufacturer's recommendations

STORAGE INSTRUCTIONS

Store upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

- Appearance** : Amber liquid
- Odour** : Characteristic
- Solubility** : Insoluble in water





TECHNICAL DATA

Veedol Syntron TGDI 5W-30

1 Litre

Flammability	:	Non Flammable
Percentage of Base Oil	:	84.09
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.37
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.28
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			61.51
Density	ASTM D792	@ 15°C			0.852

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

