



# TECHNICAL DATA

## Veedol SYNTRON LONGLIFE III 5W/30

1 Litre

### PRODUCT DESCRIPTION

Veedol SYNTRON LONGLIFE III 5W/30 is a fully synthetic engine oil formulated to provide outstanding performance levels both in terms of engine cleanliness and fuel economy. The product is recommended by Granville Oil & Chemicals Ltd for use in Volkswagen, Audi, Seat and Skoda engines requiring a VW specification oil. SYNTRON LONGLIFE III 5W/30 is fully compatible with exhaust after treatment devices such as diesel particulate filters.

### RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3  
VW: 504.00 & 507.00  
API: SN/CF  
BMW: LL-04  
MB: 229.51 & MB229.52  
Porsche: C30

SIZE	PART NO	BARCODE
1 Litre	1127	5020618011279

### PRODUCT BENEFITS

- \* Effective environmental protection
- \* Outstanding fuel efficiency
- \* Excellent high & low temperature performance
- \* Ensures lubricant performance over extended drain intervals

### PRODUCT USAGE

VAG engine types.

### DIRECTIONS FOR USE

As recommended by the engine manufacturer



AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS



## Veedol SYNTRON LONGLIFE III 5W/30 1 Litre

### STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place

### SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.07
Total Base Number	ASTM D2896	mg KOH/g	7		8.33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°C		-36	
NOACK Volatility	ASTM D5800	%		<10	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			59.81
Density	ASTM D792	@ 15°C			0.852

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

